

IMPLEMENTED: 01/01/1998 REVISED: 01/10/2025

SAFETY DATA SHEET - 16 SECTIONS

SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

<u>Product Identifier:</u> Perlite (All Grades)

PA-Lite, A-20, Ecoperl, English Mix, Gladstone, Luna Rock, Trapcoat, Cryogenic Perlite PF-65, PFF-10, PFF-18, PFF-24, ADP, BHF, Plaster Aggregate, Concrete, Screened Plaster, Blockfill,

Poolbase, PF30Y

<u>Product Use:</u> Light weight aggregate, Horticultural aggregate, Refractory,

Insulation, Filter aid.

<u>Producer and Supplier:</u> Pennsylvania Perlite Corporation

1428 Mauch Chunk Road Bethlehem, PA 18018

USA

Telephone: +1 610-868-0992

Fax: +1 610-868-7609

Date SDS Prepared: 01/10/2025 SDS Prepared By: Jose Abud

SECTION 2 – HAZARD INFORMATION

Route of Entry: Skin Contact, Inhalation

Emergency Overview:

This product may contain crystalline silica (less than 0.1%). OSHA considers Perlite a nuisance dust and recommends a PEL of 5mg/m3 TWA respirable dust. Inhalation over long periods of high amounts of any nuisance dust may overload lung clearance mechanism and make the lungs more vulnerable to respiratory disease. Long term inhalation of respirable crystalline silica can cause disabling lung disease (silicosis).

WHMIS Symbols: Not Regulated

Potential Health Effects:

<u>Inhalation</u>: Pre-existing upper respiratory and lung disease may be aggravated. Acute inhalation can cause dryness of the nasal passage and lung congestion, coughing and general throat irritation. Chronic inhalation of dust should be avoided.

Eye: May cause irritation (tear formation and redness) if dust gets in eyes.

Skin: Not absorbed by the skin, but may cause dryness if prolonged exposure.

<u>Ingestion</u>: Ingestion of small to moderate quantities is not considered harmful, but may cause irritation of the mouth, throat and stomach.



IMPLEMENTED: 01/01/1998 REVISED: 01/10/2025

SECTION 3 – CHEMICAL COMPOSITION

Hazardous Ingredients (specific)	%	CAS Number	LD of Ingredient (specify species and route)	LC of Ingredient (specify species and route)	OSHA PEL (mg/m3)	ACGIH TLV (mg/m3)
Perlite	100	93763-70-	Not	Not	10	15
		3	Available	Available		
Silica	<1	14808-60-	Not	Not	Not	.05
		7	Available	Available	Available	

SECTION 4 – FIRST AID PROCEDURES

Inhalation: Exit from dust area; drink water to clear throat; blow nose to evacuate

dust

<u>Eye Irritation:</u> Do not rub eyes. Flush eyes with copious amounts of water to remove

any dust particles. Contact a physician if irritation persists.

<u>Skin Irritation:</u> None <u>Ingestion:</u> None

SECTION 5 – FIRE AND EXPLOSION HAZARDS

None. Perlite is an inert particle and is non-flammable. Perlite melts at 2,700° F.



IMPLEMENTED: 01/01/1998 REVISED: 01/10/2025

SECTION 6 – ACCIDENTAL RELEASE MEASURES

<u>Personal Prevention:</u> The wearing of an approved respirator and safety eyewear

are recommended.

<u>Ecology Prevention</u>: None. Perlite can be used as a soil conditioner. Not considered as

hazardous waste by RCRA (40 CFR Part 261).

Spill and Leak Procedure: Vacuum clean or wet sweep, avoid dusting, use a dust

suppressant when sweeping.

SECTION 7 – HANDLING AND STORAGE

should be worn when dust is present.

Store in a dry place and away from hydrofluoric acid. Repair all broken bags immediately. Avoid creating dust. Maintain good housekeeping practices. Collect dust in a closed bag or container and/or use water to reduce airborne dust.

SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTIONS

Exposure Limits:	☑ ACGIH TLV ☑ OSHA PEL ☐ Other (Specify)
Ventilation:	Use adequate exhaust ventilation and/or dust collection to
	keep dust levels below PEL.
Personal Protective Equipment:	□ Gloves □ Respirator □ Eye □ Footwear □ Clothes
	□ Other
Goggles:	Normally not required. May use safety eyewear to protect
	from dusts.
Gloves:	Normally not required. May use gloves to protect overly-
	sensitive skin.
Respiratory: Respirators fitted with	ofilters certified to standard 42CFR84 under series N95



IMPLEMENTED: 01/01/1998 REVISED: 01/10/2025

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Odor and Appearance:	Odor Threshold (ppm):	
Solid	White Granules or Powder.	N/A	
	No distinct odor.		
Specific Gravity:	Vapor Density (air =1):	Vapor Pressure (mmHg):	
Unexpanded: 2.35	N/A	N/A	
Expanded: 0.032 - 0.160			
Evaporation Rate:	Boiling Point (C°):	Freezing Point (C°):	
N/A	N/A	N/A	
рН	Coefficient of Water/Oil	Solubility in Water:	
6-10	Distribution:	Slightly Soluble	
	N/A		

SECTION 10 – STABILITY AND REACTIVITY

<u>Stability:</u> Material is stable. Hazardous polymerization will

not occur.

<u>Chemical Incompatibilities:</u> Hydrofluoric Acid

<u>Conditions to Avoid:</u> None in designed use. Avoid contact with

hydrofluoric acid.

Hazardous Decomposition Products: Reacts with hydrofluoric acid to form toxic silicon

tetrafluoride gas.



IMPLEMENTED: 01/01/1998 REVISED: 01/10/2025

SECTION 11 – TOXICOLOGY

Effects of Acute Exposure:

Potential irritant for skin contact, eye contact or inhalation. Effects of Chronic Exposure: Perlite is a naturally occurring volcanic glass consisting of fused sodium-potassium-aluminum silicate. Test conducted on Perlite have not identified crystalline silica as being present above the detection limit (0.05%). Although here are not published reports of adverse health effects from exposure to perlite dust, dust levels should be maintained below the OSHA Permissible Exposure Limit for perlite and respirators used when airborne dust is present.

Potential irritant for skin contact, eye contact, or inhalation. Irritancy of Product:

Skin Sensitization: Possible through skin contact.

See section 8 Respiratory sensitization:

N/A Carcinogenicity –IARC: Carcinogenicity –ACGIH: N/A Reproductive Toxicity: N/A Teratogenicity: N/A Embrotoxicity: N/A N/A Mutagenicity: Name of synergisitic products/effects: N/A

SECTION 12 – ECOLOGICAL DATA

Generally considered inert. Perlite has no negative ecological effects and may be used as a soil conditioner.

SECTION 13 – DISPOSAL CONSIDERATIONS

Not considered a hazardous material by the RCRA (40 CFR Part 261). Dispose of in approved landfill. Keep moist or cover with earth. Dispose of in accordance with Federal, State, and Local regulations.



IMPLEMENTED: 01/01/1998 REVISED: 01/10/2025

SECTION 14 – TRANSPORT INFORMATION

Keep dry and avoid fugitive particles in the environment.

SECTION 15 – REGULATORY INFORMATION

WHMIS Classification: N/A SERA: Not Listed

OSHA: Perlite is not considered as a toxic or hazardous subject. TSCA: Status, Not Listed. Naturally occurring substance.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Registration number: Exempt according to Article 2 §7 b of REACH

SECTION 16 – OTHER INFORMATION

NOTICE: This information relates only to the material designated and may not be valid for such material used in combination with any other materials or in any process. All statements, information, and data provided are believed to be accurate and reliable, but are presented without any guarantee, representation, warranty, or responsibility of any kind, expressed or implied. Any and all representations and/or warranties of merchantability of fitness for a particular purpose are specifically disclaimed. Users should make their own investigations as to the suitability of the information or product for their particular purpose. Nothing in this document is intended as permission, inducement or recommendation to violate any laws or practice any invention covered by existing patents, copyrights or inventions. Pennsylvania Perlite Corporation does not accept liability for any loss or damage that may occur for the use of this information.

THIS SHEET IS BASED ON TODAY'S BEST AVAILABLE INFORMATION AND ACCORDING TO DIRECTIVE 2001/58/EC OF THE COMMISSION OF 27/07/2005.